

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner has not been previously set.

DIAGRAM

T9S R31E

S1/16

S15 | S14

1989

PLS 699

Description of corner evidence found:
Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/4" aluminum cap, marked as shown in the diagram, 26" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock to be 30" in diameter by 4" high around the monument, from which new BTs are:

11" Ponderosa pine bears S49°30'W, 75.9 feet scribed S1/16 S15 BT

9" Ponderosa pine bears S8°30'E, 140.4 feet scribed S1/16 S14 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set a steel fence post 5 feet N of the corner with a Land Survey Monument sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877,
do hereby certify that on November 19, 1989, I
established the corner as herein described.


REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
JULY 9, 1985
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 26 DAY OF July, 1990



Grant County Surveyor