

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

DIAGRAM

T9S R31E

1/4

S22 | S23

1989

PLS 699

Set a pine post for 1/4 sec. cor. from which a Pine 20 ins. diam., bears N46°E, (100.32') 152 lks. dist. Pine 6 ins. diam., bears N37°W, (42.24') 64 lks. dist.

Description of corner evidence found:

Found a mound of stone not of record at the proper corner location as measured from the bearing trees.

- 30" Ponderosa pine (16" Stump)(Scribing Visible)(1881 BT) bears N46°E, 100.2 feet.
- 31" Ponderosa pine (Good Condition)(Blaze Opened by Others)(1881 BT) bears N39°W, 42.1 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock from the BTs. Built a mound of rock to be 30" in diameter by 4" high around the monument, from which new BTs are:

- 11" Ponderosa pine bears S6°30'W, 26.5 feet scribed 1/4 S22 BT
- 14" Ponderosa pine bears S87°45'E, 49.7 feet scribed 1/4 S23 BT
- A Silver DEEP buried 6" in the ground bears N6°30'E, 2.0' with a brass washer inside stamped PLS 699
- A Blue DEEP buried 6" in the ground bears N37°45'W, 2.0' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 21, 1989, I monumented the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

*Leland L. Myers*

OREGON JULY 9, 1965 LELAND LEE MYERS 699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 26 DAY OF July, 1990

*Robert D. Boyett*

Grant County Surveyor