

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881. Set a basalt stone 12x10x5 and made mound of stone for cor. to sec's. 21, 22, 27, 28 from which a Pine 9 ins. diam., bears N47°W, (34.98') 53 lks. dist.

DIAGRAM

T9S R31E

S21 | S22  
-----  
S28 | S27

1989  
PLS 699

Description of corner evidence found:

Could not find any evidence of the mound or bearing tree after an intensive search. Numerous visits were made to the area, but to no avail. The corner area is relatively flat and undisturbed by logging or other activity. Was very frustrating to not find any evidence of this corner. 9" Pine (1881 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 24" in the ground, at double proportionate measurements from adjacent found corners. Built a mound of rock to be 36" in diameter by 6" high around the monument, from which new BTs are:

- 11" Ponderosa pine bears S46°E, 86.1 feet scribed T9SR31E S27 BT
- 9" Douglas-fir bears S8°W, 14.0 feet scribed T9SR31E S28 BT
- 7" Douglas-fir bears N56°W, 38.3 feet scribed T9SR31E S21 BT
- 9" Douglas-fir bears N48°15'E, 20.1 feet scribed T9SR31E S22 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet S of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 30, 1989, I re-established the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR  
THIS 26 DAY OF July, 19 90

Leland L. Myers  
Grant County Surveyor

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699