

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

DIAGRAM

Set a pine post for 1/4 sec. cor. from which a  
A Tamarack 24 ins. diam., bears N25°W, (23.10') 35 lks. dist.  
A Fir 40 ins. diam., bears S70°W, (26.40') 40 lks. dist.

T9S R31E

S22  
1/4—  
S27

1989  
PLS 699

Description of corner evidence found:

None of the original post was found.

A very rotted stump(1881 BT) bears at record The tree is rotted away with only the root and root collar remaining.  
A very rotten White fir (Down & Rotting Away)(Blaze in Rotted Remains)(1881 BT) bears at record

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 26" in the ground, at the point determined by the bearing trees. Built a mound of rock to be 30" in diameter by 4" high around the monument, from which new BTs are:

- 14" Douglas-fir bears N73°E, 19.4 feet scribed 1/4 S22 BT
- 14" Douglas-fir bears S27°E, 35.8 feet scribed 1/4 S27 BT
- An Orange DEEP buried 8" in the ground bears N27°W, 2.0' with a brass washer inside stamped PLS 699
- A Blue DEEP buried 8" in the ground bears S73°W, 2.0' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet E of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 25, 1989, I monumented the corner as herein described.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR  
THIS 26 DAY OF July, 1990

Robert D. Sargent  
Grant County Surveyor