

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.
Set a basalt stone 24x12x8 and made mound of stone for 1/4 sec. cor. from which a Pine 16 ins. diam., bears S88°E, (8.58') 13 lks. dist.

DIAGRAM

T9S R31E

1/4
S28 | S27

1989
PLS 699

Description of corner evidence found:

Found a pile of shaley stone alongside a rock outcrop at the proper distance from the bearing tree. The corner stone apparently has split into thinner stones. No markings could be found on the stones.
23" Ponderosa pine (Fair Condition)(Blaze Opened by Others)(1881 BT) bears N80°30'E, 9.0 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 22" in the ground to solid rock, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock to be 36" in diameter by 8" high around the monument, from which new BTs are:

- 6" Juniper bears S10°15'E, 31.3 feet scribed 1/4 S27 BT
- 13" Juniper bears S43°45'W, 48.2 feet scribed 1/4 S28 BT

An Orange DEEP buried 6" in the ground bears N10°15'W, 6.0' with a brass washer inside stamped PLS 699

A Silver DEEP buried 6" in the ground bears N43°45'E, 3.2' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet N of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 17, 1989, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 26 DAY OF July, 1990

Robert D. Sayre
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland Lee Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699