

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

DIAGRAM

Set a pine post for cor. to secs. 28, 29, 32, 33 from which a

- Pine 36 ins. diam., bears N51°E, (63.36') 96 lks. dist.
- Pine 9 ins. diam., bears N51°W, (44.88') 68 lks. dist.
- Pine 9 ins. diam., bears S68°W, (64.68') 98 lks. dist.
- Pine 30 ins. diam., bears S45°E, (1.32') 2 lks. dist.

T9S R31E

S29 | S28

S32 | S33

1912
PLS 699

Description of corner evidence found:

Found no evidence of the original post, however a fence corner is very near the corner position.

- Rotten Ponderosa pine (Down & Rotting Away)(Blaze in Rotted Remains)(1881 BT) bears at record.
- 16" Ponderosa pine (Good Condition)(Blaze Opened by Others)(1881 BT) bears S68°15'W, 63.8 feet.
- 36" Ponderosa pine (20" high Stump)(Blaze and chaining notch)(1881 BT) bears S45°E, 4.3 feet. Present distance to center of stump.
- 36" Pine (1881 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground, at the point determined by the bearing trees. Built a mound of rock to be 30" in diameter by 6" high around the monument, from which new BTs are:

- 5" Ponderosa pine bears S16°30'E, 25.2 feet scribed T9SR31E S33 BT
- 12" Douglas-fir bears S69°15'W, 54.9 feet scribed T9SR31E S32 BT
- 8" Douglas-fir bears N74°45'W, 31.3 feet scribed T9SR31E S29 BT
- 6" Ponderosa pine bears N76°E, 44.8 feet scribed T9SR31E S28 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet E and 5 feet N of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the E post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 12, 1989, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 26 DAY OF July, 1990

Robert D. Bayliff
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers
OREGON
JULY 9, 1965
LELAND LEE MYERS
699