

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:  
Corner has not been previously set.

DIAGRAM

T9S R31E

S27  
E1/16—  
S34

1989  
PLS 699

Description of corner evidence found:  
Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 26" in the ground to hardpan, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. No rocks available to build a mound, from which new BTs are:

13" Ponderosa pine bears S39°45'E, 23.6 feet scribed E1/16 S34 BT

11" Ponderosa pine bears N82°15'E, 17.9 feet scribed E1/16 S27 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 24, 1989, I established the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR  
THIS 26 DAY OF July, 1990

*[Signature]*  
Grant County Surveyor

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*[Signature]*

OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699