CERTIFIED RECORD OF LAND CORNER MONUMENTATION

DIAGRAM

T9S R31E

1/4

S34 | S35

1989
PLS 699

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

Set a pine post for 1/4 sec. cor.

A pine 40 ins. diam., bears N35°E, (45.54') 69 lks. dist.

A pine 26 ins. diam., bears N45°W, (58.08') 88 lks. dist.

Description of corner evidence found:

No evidence of the original post was found.

46" Ponderosa pine (30" Stump)(Scribing Visible)(1881 BT) bears N32°30'E, 45.1 feet.

Root hole (Blaze in Rotted Remains)(1881 BT) bears at record bearing and distance.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, at the point determined by the bearing trees. Built a mound of rock to be 30" in diameter by 4" high around the monument , from which new BTs are:

15" Ponderosa pine bears S40°30'E, 10.5 feet scribed 1/4 S35 BT

11" Ponderosa pine bears S28°15'W, 12.2 feet scribed 1/4 S34 BT

An Orange Deep buried 10" in the ground bears N40°30'W, 2.0' with a brass washer inside stamped PLS 699

An Sliver Deep buried 8" in the ground bears N28°15'W, 2.0' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 22, 1989, I monumented the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 26 DAY OF July, 1990

Robert D. Sargent

Grant County Surveyor

USDA-FS Contract No. 53-04kk-8-02421

151

T9S R31E X-17