

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Herman D. Gradon, US Deputy Surveyor, during the original survey Joint Contract No. 416 dated August, 1881.

Set basalt stone 16x9x6 ins. 11 ins. in the ground for 1/4 sec. cor. marked 1/4 on W face; from which

A pine 24 ins diam bears S54°E, (54.8')83 lks dist. marked 1/4 S BT

A pine 36 ins diam bears S80°W, (19.1')29 lks dist. marked 1/4 S BT

DIAGRAM

T9S R32E

1/4
S10 | S11

1986
PLS 699

Description of corner evidence found:

18x9x8 stone setting vertically in a ring of stones, but do not find any markings on the stone. Possibly is a new stone as it appears that a skid road passed over the corner location. The found stone checks with the bearing trees.

24" Ponderosa pine (Dead & Down)(Scribing Visible)(1881 BT) bears at record

36" Ponderosa pine (12' Broken Stub)(Blaze side of tree completely burned away)(1881 BT) bears S86°W, 20.7 feet

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 26" in the ground, at the unmarked rock and checked by the bearing trees. Built a mound of rock & earth to be 30" in diameter by 6" high around the monument, from which new BTs are:

9" Ponderosa pine bears S11° 15'W, 8.2 feet scribed 1/4 S10 BT

8" Ponderosa pine bears S44° 30'E, 20.8 feet scribed 1/4 S11 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to stamped brass washers nailed in the scribed red-painted blazes.

Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on August 18, 1986, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1985
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 23 DAY OF Feb, 1987

Robert D. Bugh
Grant County Surveyor