

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner has not been previously set.

DIAGRAM

T9S R32E

N1/16
S15 | S14

1986
PLS 699

Description of corner evidence found:

Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock to be 30" in diameter by 6" high around the monument, from which new BTs are:

13° Ponderosa pine bears N18°W, 79.2 feet scribed N1/16 S15 BT

8° Ponderosa pine bears N68°E, 26.4 feet scribed N1/16 S14 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet E and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the E post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on September 22, 1986, I established the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
JULY 9 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE GRANT COUNTY SURVEYOR

THIS 23 DAY OF Feb, 1987


Grant County Surveyor