

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original corner was set in 1881 by Rufus S. Moore under Contract No. 382, dated March 23, 1881. The original notes state: North on the E. bdy of Sec 36 80.00 Set a basalt stone 20x10x10 in a mound of stone for cor to secs25,30,31,36.

DIAGRAM

T9S
R31E R32E
S25|S30
---+---
S36|S31

Description of corner evidence found:

Found a 19x12x7 stone in a mound of stone , 3 notches on the East side, top to South.

Description of monument and accessories I establish to perpetuate the original location of this corner:


Set a 2x28" aluminum monument 3" in the ground in a mound of stone and buried the original monument on the North side. I establish new bearing trees: An 18" P.Pine bears S 9 1/2° E, 103.3 ft, scribed T9SR32ES31BT. A 10" P.Pine bears N 5 1/2° E, 71.9 ft, scribed T9SR32ES30BT. No other suitable trees within range.

T9S
R31E R32E
S25|S30
---+---
S36|S31
PLS1918
1988

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Sun Cadastral Survey, Cont No. 53-04H1-7-4011
Field Book: 4-44 & 6-55
Work accomplished: 9/7/88
Witnesses: Tyler Parsons, Louise Parsons
Job No.: 87221

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515



Office of COUNTY SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 5th day of Feb, 1989

Robert D. Dazett by _____
(COUNTY OFFICIAL) (DEPUTY)