

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner has not been previously set.

DIAGRAM

T9S R33E

SW1/16+S30

1986
PLS 699

Description of corner evidence found:

Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 22" in the ground to hardpan, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock & earth to be 30" in diameter by 8" high around the monument, from which new BTs are:

9" Douglas-fir bears N61° 15'E, 34.4 feet scribed SW1/16 S30 BT

5" Ponderosa pine bears S42° 45'W, 39.6 feet scribed SW1/16 S30 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet W and 5 feet N of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on August 4, 1986, I established the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 23 DAY OF Feb, 1987

Robert D. Baggett
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699