CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

Set a basalt stone 18x10x10 and made mound of stone for 1/4 sec. cor. from which a

Fir 16 ins. diam., bears S38°E, (71.28') 100 lks. dist.

DIAGRAM

T9S R31E

S16
1/4
S21

1989
PLS 699

Description of corner evidence found:

Found a rock mound at the proper distance from the bearing tree, but not a stone of near record size. Corner is on a steep hillside with rock outcrops.

14" Douglas-fir (Dead & Down)(Scribing Visible)(1881 BT) bears S37°30'E, 71.0 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, at the point determined by the bearing tree. Improved the existing mound with rock to be 30" in diameter by 4" high around the monument, from which new BTs are:

11" Juniper bears S5°E, 45.9 feet scribed 1/4 S21 BT

9" Juniper bears N25°30'W, 47.6 feet scribed 1/4 S16 BT

A Pink DEEP buried 4" in the ground bears S25°30'E, 2.0' with a brass washer inside stamped PLS 699

An Orange DEEP buried 6" in the ground bears N5°W, 2.0' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet S and 5 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the S post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 12, 1989, I monumented the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 26 DAY OF July, 19 90

Robert D Lazzarini

Grant County Surveyor

USDA-FS Contract No. 53-04KK-8-02421

1151

T9S R31E N-11