# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

Set a fir post for 1/4 sec. cor. from which a

A Pine 24 ins. diam., bears N32°W, (56.10') 85 lks. dist.

A Fir 14 ins. diam., bears S27°W, (56.76') 86 lks. dist.

DIAGRAM

T9S R31E

S15
1/4
S22

1989
PLS 699

**Description of corner evidence found:**

None of the original post was found.

Stump Hole(1881 BT) bears at record.

Burnt stub(10' Broken Stub)(Scribing slightly visible on two blazes)(1881 BT) bears N35°30'W, 55.9 feet.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 24" in the ground, at the point determined by the bearing trees. Built a mound of rock to be 30" in diameter by 6" high around the monument , from which new BTs are:

11" Ponderosa pine bears N12°30'E, 58.1 feet scribed 1/4 S15 BT

9" White fir bears S63°E, 62.5 feet scribed 1/4 S22 BT

An Orange DEEP buried 6" in the ground bears N63°W, 2.0' with a brass washer inside stamped PLS 699

A Blue DEEP buried 6" in the ground bears S12°30'W, 2.0' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 18, 1989, I monumented the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 26 DAY OF July, 1990

Robert W. Lazett

Grant County Surveyor

USDA-FS Contract No. 53-04KK-8-02421

1151

T9S R31E N-15