CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

Set a basalt stone 16x12x10 and erected mound of stone for cor. to sec's. 22, 23, 26, 27 from which

A pine 24 ins. diam., bears N33°W, (34.32') 52 lks.

DIAGRAM

T9S R31E

S22	S23
S27	S26

1989
PLS 699

Description of corner evidence found:

Found a stone in an improved mound by an unknown party. There was no other corner evidence and this position has been accepted by the local land owners. Found no reason to not accept the stone and mound as the section corner.

24" pine (1881 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 24" in the ground to rock, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock to be 32" in diameter by 6" high around the monument, from which new BTs are:

4" Juniper bears N23°15'W, 26.2 feet scribed T9SR31E S22 BT

24" Ponderosa pine bears N58°E, 38.6 feet scribed T9SR31E S23 BT

16" Juniper bears S22°30'E, 101.9 feet scribed T9SR31E S26 BT

18" Ponderosa pine bears S53°30'W, 76.3 feet scribed T9SR31E S27 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 21, 1989, I monumented the corner as herein described.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 26 DAY OF July, 19 90

Robert D Bagett

Grant County Surveyor

USDA-FS Contract No. 53-04KK-8-02421

(15) T9S R31E R-17