A-21

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *

The original corner was set in 1881 by Rufus S. Moore under Contract No. 382, dated March 23, 1881.
The original notes state:
N 89°42'East on a true line on N bdy Sec 2
80.00 Set a basalt stone 18x12x8 and dug pits for cor to Secs 1,2,35,36

DIAGRAM

T9S R31E
S35!S36
---+---
S2!S1
T10S

Description of corner evidence found:

Found a 18x13x9" (18x12x8") stone, 6 grooves on the South side, in a mound of stone.

Description of monument and accessories I establish to perpetuate the original location of this corner:

Set a 2½X28" aluminum monument 21" in the ground in a mound of stone and buried the original stone on the South side.
I establish new bearing trees:
A 20" Juniper bears N 46¼° W, 144.0 ft, scribed T9SR31ES35BT.
A 14" double Juniper bears N 33¾° E, 163.4 ft, scribed T9SR31ES36BT.
A 9" double Juniper bears S 26° W, 72.4 ft, scribed T10SR31ES2BT.

T9S R31E
T10S
S35!S36
---+---
S2!S1
PLS1918
1988

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Sun Cadastral Survey, Cont No. 53-04H1-7-4011
Field Book: 4-16 & 5-37
Work accomplished: 7/31/88
Witnesses: Tyler Parsons, Louise Parsons
Sharon Parsons, Douglas Parsons
Job No.: 8722I

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515



Office of COUNTY SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 1st day of Feb, 19 89

Robert D Bagett by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

Z-21