3

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner set by Herman D. Graden under contract No. 416, dated August 19, 1881.

Set a basalt stone 14 x 10 x 4 9 inches in ground mkd ¼ on west face

A fir 12 ins. diam. East 72 lks mkd ¼ S BT

A pine 30 ins. diam. bears N 85°W 38 lks mkd ¼ S BT

DIAGRAM

T 9 S R 3 2 E W M

Description of corner evidence found:

Found a 36 in. diam. fir, East 47.52 feet with open blaze, markings not legible

Found a 32 in. diam. stump (1 ft. tall & burned out), N 85°W, 25.1 ft. No scribing visible

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 3" aluminum cap on 30" aluminum pipe 2" above a mound of stone 14" high x 36" x 36" mk'd

from which:

A 13" diam. ponderosa pine N 56°W, 23.3 ft. with upper blaze mkd ¼ S34

T9S R32E



Set steel guard post 5½ feet long 18" in the ground 3 feet west of corner with USFS 54-4 attached

Nailed brass washer (RLS 1859) in lower blaze.

Used Brunton compass and steel chain to measure distance and bearing.

Var. 20° E

Office of County Surveyor *County of* Grant

State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 1 *day of* April, *19* 83

Robert D Bagett *by* .....

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

X-17